

MIN 2500~6000 TL-XE

- Maximum efficiency 98.4%
- Dual MPP trackers
- Type II SPD on DC side
- Supports export control
- Touch key and OLED display



P O W E R
- I N G O
T O M O -
R R O W O

Growatt
powering tomorrow

www.ginverter.com

| Datasheet | MIN 2500TL-XE | MIN 3000TL-XE | MIN 3600TL-XE | MIN 4200TL-XE | MIN 4600TL-XE | MIN 5000TL-XE | MIN 6000TL-XE |
|--|--|---------------|---------------|---------------|---------------|---------------|---------------|
| Input data (DC) | | | | | | | |
| Max. recommended PV power (for module STC) | 3500W | 4200W | 5040W | 5880W | 6440W | 7000W | 8100W |
| Max. DC voltage | 500V | 500V | 550V | 550V | 550V | 550V | 550V |
| Start voltage | 100V | | | | | | |
| Nominal voltage | 360V | | | | | | |
| MPP voltage range | 80V-500V | 80V-500V | 80V-550V | 80V-550V | 80V-550V | 80V-550V | 80V-550V |
| No. of MPP trackers | 2 | | | | | | |
| No. of PV strings per MPP tracker | 1 | | | | | | |
| Max. input current per MPP tracker | 12.5A | | | | | | |
| Max. short-circuit current per MPP tracker | 16A | | | | | | |
| Output data (AC) | | | | | | | |
| AC nominal power | 2500W | 3000W | 600W | 4200W | 4600W | 5000W | 6000W |
| Max. AC apparent power | 2500VA | 3000VA | 3600VA | 4200VA | 4600VA | 5000VA | 6000VA |
| Nominal AC voltage (range*) | 230V (180-280V) | | | | | | |
| AC grid frequency (range*) | 50/60 Hz (45-55Hz/55-65 Hz) | | | | | | |
| Max. output current | 11.3A | 13.6A | 16A | 19A | 20.9A | 22.7A | 27.2A |
| Adjustable power factor | 0.8leading...0.8lagging | | | | | | |
| THDi | <3% | | | | | | |
| AC grid connection type | Single phase | | | | | | |
| Efficiency | | | | | | | |
| Max. efficiency | 98.2% | 98.2% | 98.2% | 98.4% | 98.4% | 98.4% | 98.4% |
| European efficiency | 97.1% | 97.1% | 97.2% | 97.5% | 97.5% | 97.5% | 97.5% |
| MPPT efficiency | 99.9% | | | | | | |
| Protection devices | | | | | | | |
| DC reverse polarity protection | yes | | | | | | |
| DC switch | yes | | | | | | |
| AC/DC surge protection | Type II / Type III | | | | | | |
| Insulation resistance monitoring | yes | | | | | | |
| AC short-circuit protection | yes | | | | | | |
| Ground fault monitoring | yes | | | | | | |
| Grid monitoring | yes | | | | | | |
| Anti-islanding protection | yes | | | | | | |
| Residual-current monitoring unit | yes | | | | | | |
| AFCL protection | Optional | | | | | | |
| General data | | | | | | | |
| Dimensions (W / H / D) | 375/350/160mm | | | | | | |
| Weight | 10.8kg | | | | | | |
| Operating temperature range | -25°C ... +60°C | | | | | | |
| Noise emission (typical) | ≤35 dB(A) | | | | | | |
| Nighttime power consumption | < 1W | | | | | | |
| Topology | Transformerless | | | | | | |
| Cooling | Natural convection | | | | | | |
| Protection degree | IP65 | | | | | | |
| Relative humidity | 0-100% | | | | | | |
| Altitude | 4000m | | | | | | |
| DC connection | H4/MC4(Optional) | | | | | | |
| AC connection | Connector | | | | | | |
| Display | OLED+LED/WIFI+APP | | | | | | |
| Interfaces: RS485 / USB/WI-FI / GPRS/ RF/LAN | Yes/Yes/Optional/Optional/Optional /Optional | | | | | | |
| Warranty: 5 years / 10 years | Yes /Optional | | | | | | |

CE, CEI 0-21, VDE-AR-N 4105, VDE 0126-1-1, UTE C 15-712-1, EN 50549, IEC 62116, IEC 61727, G99, C10/C11, UNE217001, UNE206007, PO12.2

* The AC voltage and frequency range may vary depending on specific country grid standard.
All specifications are subject to change without notice.

GROWATT NEW ENERGY TECHNOLOGY Co.,LTD A: No.28 Guangming Road, Longteng Community, Shiyan, Baoan District, Shenzhen, P.R.China.
T: + 86 755 2747 1900 F: + 86 755 2749 1460 E: info@ginverter.com